

STMicroelectronics University of Grenoble





Debugging Component-Based Embedded Applications.

Kevin Pouget, Miguel Santana, Vania Marangozova-Martin and Jean-François Mehaut



Context

Embedded System Development

- High-resolution multimedia app. ⇒ high performance expectations.
 - H.265 HEVC
 - augmented reality,
 - •
- Sharp time-to-market constraints
- → Important demand for
 - powerful parallel architectures
 - MultiProcessor on Chip (MPSoC)
 - convenient programming methodologies
 - Component-Based Software Engineering
 - efficient verification and validation tools
 - Our problematic



Context

MultiProcessor on Chip (MPSoC)

- Parallel architecture
 - more difficult to program
- Maybe heterogeneous
 - hardware accelerators,
 - GPU-like accelerators (OS-less)
- Embedded system
 - constrained environment,
 - on-board debugging complicated
 - → performance debugging only
 - limited-scale functional debugging on simulators

Context

Component-Based Software Engineering

- Focus on design of independent building blocks
- Applications built with interconnected components
- Allows the adaptation of the application architecture according to runtime constraints
- Runnable components able to exploit MPSoC parallelism

Agenda

1 Component Debugging Challenges

2 Component-Aware Interactive Debugging

§ Feature Demonstration

4 Conclusion



Agenda

1 Component Debugging Challenges


2 Component-Aware Interactive Debugging

3 Feature Demonstration

4 Conclusion


Component-based applications are dynamic

- various set of components deployed during the execution
- components are dynamically inter-connected




Component-based applications are dynamic

- various set of components deployed during the execution
- components are dynamically inter-connected




Component-based applications are dynamic

- various set of components deployed during the execution
- components are dynamically inter-connected




- their execution is driven by interface communications
- complex framework-dependent steps between an interface call and its execution

- their execution is driven by interface communications
- complex framework-dependent steps between an interface call and its execution






- their execution is driven by interface communications
- complex framework-dependent steps between an interface call and its execution






- their execution is driven by interface communications
- complex framework-dependent steps between an interface call and its execution






- their execution is driven by interface communications
- complex framework-dependent steps between an interface call and its execution






- their execution is driven by interface communications
- complex framework-dependent steps between an interface call and its execution






- their execution is driven by interface communications
- complex framework-dependent steps between an interface call and its execution






- their execution is driven by interface communications
- complex framework-dependent steps between an interface call and its execution







Information flows over the components




Information flows over the components




Information flows over the components




Information flows over the components



Information flows over the components



Information flows over the components



Agenda

① Component Debugging Challenges

2 Component-Aware Interactive Debugging

3 Feature Demonstration


4 Conclusion

Objective: Bring the debugger closer to the component model

- Show application architecture evolutions
 - component deployment
 - interface binding
 - •
- Follow the execution flow(s) over the component graph
 - runnable component execution,
 - execution triggered by an interface call
 - •
- Track inter-component data exchanges
 - payload contents
 - data paths
 - •


Result: high-level primitives for execution control and state examination

Implementation



Implementation


⇒ Detect and interpret key events in the component framework






Component

Implementation





Implementation











Implementation



Implementation


⇒ Detect and interpret key events in the component framework





Component

Implementation












Implementation












Implementation

⇒ Detect and interpret key events in the component framework








Component

Implementation












Implementation








Implementation

⇒ Detect and interpret key events in the component framework










Component

Implementation












Implementation












Implementation












Implementation











Agenda

① Component Debugging Challenges


Component-Aware Interactive Debugging

§ Feature Demonstration

Proof-of-concept environment

Platform 2012

- Heterogeneous
- 4x16 CPU OS-less comp. fabric




Proof-of-concept environment

Native Programming Mode

- P2012 component framework
- Provides communication components and interface

Platform 2012

- Heterogeneous
- 4x16 CPU OS-less comp. fabric



Proof-of-concept environment

The Gnu Debugger

- Adapted to low level debugging
- Large user community


Native Programming Model

- P2012 component framework
- Provides communication components and interface

Platform 2012

- Heterogeneous
- 4x16 CPU OS-less comp. fabric





Proof-of-concept environment

The Gnu Debugger


- Adapted to low level debugging
- Large user community

Native Programming Model

- P2012 component framework
- Provides communication components and interface


Platform 2012

- Heterogeneous
- 4x16 CPU OS-less comp. fabric



Case study: Debugging a Pyramidal Feature Tracker

- part of an augmented reality application
- analyzes video frames to track interesting features motion







Host Fabric


SmoothAndSample
Component

```
(gdb) info component +connections
#1 Host[31272]
        DMAPush/Ox... <DMA> srcPullBuffer Component... #2
        DMAPull/Ox... <DMA> dstPushBuffer Component... #2
        ...
# #2 Component [SmoothAndSampleProcessor.so]
        srcPullBuffer <DMA> DMAPush/Ox... Host[31272]
```

dstPullBuffer <DMA> DMAPull/0x... Host[31272]

Slide 16/21 — Kevin Pouget et al. — Debugging Component-Based Embedded Applications. — May 15, 16 2012


Information about messages



Message 1:

Component A # Message created

Information about messages




Message 1:

Component A # Message created

Component A:: Interface A.1 # Message sent

Information about messages




Message 1:

Component A # Message created

Component A:: Interface A.1 # Message sent

Information about messages




```
Message 1:
```

Component A # Message created

Component A::Interface A.1 # Message sent


Component B::Interface B.1 # Message received

Information about messages



```
Message 1:
Component A # Message created
Component A::Interface A.1 # Message sent
Component B::Interface B.1 # Message received
Message 2:
Component B # Message created
```

Information about messages



Message 1:

Component A # Message created

Component A::Interface A.1 # Message sent


Component B::Interface B.1 # Message received

Message 2:

Component B # Message created Component B::Interface B.2 # Message sent




Information about messages



```
Message 1:
Component A # Message created
Component A::Interface A.1 # Message sent
Component B::Interface B.1 # Message received
Message 2:
Component B # Message created
Component B::Interface B.2 # Message sent
Component C::Interface C.1 # Message received
```




Information about messages



```
Message 1:
Component A # Message created
Component A::Interface A.1 # Message sent
Component B::Interface B.1 # Message received
Message 2:
Component B # Message created
Component B::Interface B.2 # Message sent
Component C::Interface C.1 # Message received
```



Information about messages




messages can be logically aggregated with user-defined routing tables:

```
Message 1:
Component A # Message created
Component A::Interface A.1 # Message sent
Component B::Interface B.1 # Message received
Message 2:
Component B # Message created
Component B::Interface B.2 # Message sent
Component C::Interface C.1 # Message received
```



Information about messages




 messages can be logically aggregated with user-defined routing tables:

```
Message 1:
Component A # Message created
Component A::Interface A.1 # Message sent
Component B::Interface B.1 # Message received
Component B::Interface B.2 # Message sent
Component C::Interface C.1 # Message received
```




Information about interface activity



```
(gdb) info components +counts
#2 CommComponent[SmoothAndSampleProcessor.so]
    srcPullBuffer #35 msgs
    dstTmpPushBuffer #36 msgs
    srcTmpPullBuffer #35 msgs
    dstPushBuffer #34 msgs
```



Information about interface activity



```
(gdb) info components +counts
#2 CommComponent[SmoothAndSampleProcessor.so]
    srcPullBuffer #35 msgs
    dstTmpPushBuffer #36 msgs
    srcTmpPullBuffer #35 msgs
    dstPushBuffer #34 msgs
```

 allowed us to find a bug in the application (msg sent to the wrong interface)

Case study: Debugging a Pyramidal Feature Tracker Information about interface activity

Excerpt from a 300 lines-of-code file

```
/* Compute last lines if necessary */
if (tmp_size > 0) {
    ...
    /* Transmit the last lines computed */
    CALL(srcTmpPullBuffer, release)(...);
    CALL(dstTmpPushBuffer, push)(...);
}
```

Agenda

① Component Debugging Challenges

2 Component-Aware Interactive Debugging

3 Feature Demonstration

- Debugging dynamic component application is challenging
- No high level information about components
- Our contribution: bring debuggers closer to the component model
 - better understanding application behavior
 - keep focused on bug tracking

- Debugging dynamic component application is challenging
- No high level information about components
- Our contribution: bring debuggers closer to the component model
 - better understanding application behavior
 - keep focused on bug tracking
- Proof-of-concept: GDB/Python, widely used in embedded development
- Going further programming-model aware debugging
 - OpenCL,
 - Dataflow execution model.
 - . . .